

# M.S. HOEGH CARIBIA

# PARTICULARS

Tonnage	Gross	Net
International(Register)	20 209 T	6 062 T
Suez Canal	21 918 cub feet	19 873 cub feet
Panama Canal(PC/UMS)	68 116 cub feet	19601 cub feet
Dead Weight(Summer)	4 674 MT	Design/Scantling
Light Weight	6 885 MT	-

Type, Class & Port of Registry etc		
Type	PCTC	
Class	BV AUT-UMS, Ice class 1C	
Class ID No	30504	
T/C Owner	N/A	
Registered Owner	Gram Car Carriers Holdings Pte Ltd	
Ship Managing Company	OSM Ship Management Pte. Ltd	
Manning Company	OSM Crew Management Ltd.	
Port of Registry	Singapore	
Flag	Singapore	
Date of Keel Laid	18 Sep 08	
Date of Launching	21 Sep 2009	
Date of Delivery	07 Jan 2010	
IMO Number(Lloyds Code)	9407665	
Official Number	395132	
Call Sign	9V7983	
Sat-C Telex	456515910	
Sat-C E-mail	<a href="mailto:456515910@inmc.eik.com">456515910@inmc.eik.com</a>	Text e-mail only
E-Mail	<a href="mailto:master@hoegh-caribia.osm.no">master@hoegh-caribia.osm.no</a>	Master
E-Mail	<a href="mailto:bridge@hoegh-caribia.osm.no">bridge@hoegh-caribia.osm.no</a>	Bridge
VSAT Tel	+ 65 3158 4952	Master
VSAT Tel	+ 65 3158 4953	Bridge
FBB Tel	+ 870 773 804 699	Bridge
Builder	Kyokuyo Shipyard Corporation, Japan	

Principal Dimension		
L.O.A.	139,99 m	
L.P.P.	131,00 m	
Breadth(Mould)	22,40 m	
Depth (Mould)	17,30 m	
Draft(EXT. Summer)	5,6/6,1 m	Design/Scantling

Machinery	
Main Engine(maker/type)	2 x MAK 6M43C
Output	10 800 kw
Diesel Generator(maker/type)	Daihatsu Diesel 6 DC-17A 2 400 kw

Speed & Endurance		
Service Speed(C/P)	18	Knots
F.O.Consumption(for M/E)	36	MT/day
Endurance	10 000	Miles

Fuel Type		
Spec(FO)	380	cst (CIMAC H35)
Spec(DO)	MDO	(ISO-F-DMB)

Tank Capacity		
W.B.T.	3 251,5	cbm
F.W.T.	134,7	cbm
F.O.T.	1 147,2	cbm
D.O.T.	100,3	cbm

Side Thruster		
Bow Thruster	1 300	kw
Stern Thruster	not fitted	kw

Car Handling Equipments		
Stern Ramp		
Position	Stern	
Size	15,9 x 7 (effective)	
Opening Size	4,8 (H) x 8,5 (W)	
Load Base	75	tons
Stern Quarter Ramp		
Position	Starboard	
Size	16,3 x 5,0 (effective)	
Opening Size	8,45 (H) x 4,8 (W)	
Load Base	50	tons

Cargo Capacity				
Deck	Clear height (m)	Type of deck	SQM	Uniform load (tons/m <sup>2</sup> )
Upper decl 1,9		Fixed	1 978	0,20
No. 6	2,2	Fixed	2 657	0,20
No. 5	2,2	Fixed	2 490	0,20
No. 4	2,3	Fixed	2 567	0,20
No. 3	2,40/2,00/1,70	Liftable	2 447	0,20
No. 2	2,40/2,80/3,10/4,80	Fixed	2 275	2,00
No. 1	2,2	Fixed	960	0,75
Tank top	2,0	Tank top	751	0,75
Total m <sup>2</sup>			16 125	