

# Viking Bravery

# PARTICULARS

Tonnage	Gross	Net
International(Primary)	62 106 T	20 053 T
Suez Canal	T	T
Panama Canal(PC/UMS)		
Dead Weight(Summer)	18 372 T	(scantling draught)
Light Weight	17 825 T	

Type, Class & Port of Registry etc		
Type	PCTC	
Class	DNV	
Class ID No		
T/C Owner	N/A	
Registered Owner	Global Adventure Pte Ltd	
Ship Managing Company	OSM Singapore	
Manning Company	OSM Singapore	
Port of Registry	Singapore	
Flag	Singapore	
Date of Keel Laid	06 May 2014	
Date of Launching	22 October 2014	
Date of Delivery	30 April 2015	
IMO Number(Lloyds Code)	9673020	
Official Number	399862	
Call Sign	9V3164	
Sat-C Telex	456580610	
Sat-C E-mail	<a href="mailto:456580610@inmc.eik.com">456580610@inmc.eik.com</a>	Text e-mail only
E-Mail	<a href="mailto:master@viking-bravery.osm.no">master@viking-bravery.osm.no</a>	Master
E-Mail	<a href="mailto:bridge@viking-bravery.osm.no">bridge@viking-bravery.osm.no</a>	Bridge
VSAT Tel	+ 44 1322 788 282	Master
VSAT Tel	+ 65 3163 2709	Bridge
FBB Tel	+ 870 773 935 187	Bridge
Builder	CSC JINLING SHIPYARD	

Principal Dimension	
L.O.A.	199,900 m
L.P.P.	190,000 m
Breadth(Mould)	32,260 m
Scantling draught (Mould)	10,000 m

Machinery	
Main Engine(maker/type)	MAN B&W 6S60 ME-C8.2 Tier II
Output	12 200 kw
Diesel Generator(maker/type)	3 x MAN 1 200 kw each

Speed & Endurance		
Service Speed(C/P)	16	Knots
F.O.Consumption(for M/E)	30	MT/day (HFO)
Endurance	20 000	Miles

Fuel Type		
Spec(FO)	380	cst
Spec(DO)		

Tank Capacity		
W.B.T.	6 400,0	cbm
F.W.T.	300,0	cbm
F.O.T.	3 000,0	cbm
D.O.T.	300,0	cbm

Side Thruster		
Bow Thruster	1 800	kw
Stern Thruster	not fitted	kw

Car Handling Equipments		
Stern Quarter Ramp		Starboard Quarter
Position		
Size		31,5 x 7.5m driveway width
Opening Size		12 m (B) x 5.4m/3.34/2.80 (H)
Load Base	150	tons
Side Ramp		Starboard
Position		
Size		21.5 x 4.5 driveway width
Opening Size		5,4 (B) x 5.88/2.8/3.34
Load Base	22	tons

Cargo Capacity					
Deck	Clear height (mm)	Type of deck	SQM	Axle load (t)	Uniform load (tons/m²)
12	2000	Fixed	5572	1,6/2	0,25
11	2000	Fixed	5716	1,6/2	0,3
10	2000	Fixed	5716	1,6/2	0,25
9	2200	Fixed	5716	1,6/2	0,3
8	1700/2100	Liftable	5716	1,6/2	0,3
7	2200/2600/4300	Fixed	4998	15/2	0,75
6	1900/2400	Liftable	5294	1,6/2	0,3
5	2800/3340/5200	Fixed	5133	25/2 & 55/4	2,5
4	2400	Liftable	3645	16,2	0,3
3	2200/4600	Fixed	3551	15/2 & 25/4	2
2	1700	Liftable	3046	1,6/2	0,3
1	2000/3700	Fixed	2691	15/2	1
Total m²			56 794		