

Viking Adventure

PARTICULARS

Tonnage	Gross	Net
International(Primary)	62.106 T	20.053
Suez Canal	65.413 T	61.319
Panama Canal(PC/UMS)		-
Japanese Tonnage Certificate	38.878	
Dead Weight(Summer)	18.372	(scantling draught)
Light Weight	17.825,0	

Type, Class & Port of Registry etc		
Type	PCTC	
Class	DNV	
Class ID No	32932	
T/C Owner	N/A	
Registered Owner	Global Adventure Pte Ltd	
Ship Managing Company	OSM Singapore	
Manning Company	OSM Singapore	
Port of Registry	Singapore	
Flag	Singapore	
Date of Keel Laid	16 January 2014	
Date of Launching	15 July 2014	
Date of Delivery	29 January 2015	
IMO Number(Lloyds Code)	9673018	
Official Number		
Call Sign	9V3165	
Sat-C Telex	456582410	
Sat-C E-mail	456582410@inmc.eik.com	Text e-mail only
E-Mail	master@viking-adventure.osm.no	Master
E-Mail	bridge@viking-adventure.osm.no	Bridge
VSAT Tel	+ 44 1322 788 287	Master
VSAT Tel	+ 44 1322 788 288	Bridge
VSAT Tel	+ 65 3163 2726	Bridge
FBB Tel	+ 870 773 935 363	Bridge
Builder	CSC JINLING SHIPYARD	

Principal Dimension	
L.O.A.	199,900 m
L.P.P.	190,000 m
Breadth(Mould)	32,260 m
Scantling draught (Mould)	10,000 m

Machinery	
Main Engine(maker/type)	MAN B&W 6S60 ME-C8.2 Tier II
Output	12.200 kw
Diesel Generator(maker/type)	3 x MAN 1.200 kw each

Speed & Endurance		
Service Speed(C/P)	16	Knots
F.O.Consumption(for M/E)	30	MT/day (HFO)
Endurance	20.000	Miles

Fuel Type		
Spec(FO)	380	cst
Spec(DO)		

Tank Capacity		
W.B.T.	6.400,0	cbm
F.W.T.	300,0	cbm
F.O.T.	3.000,0	cbm
D.O.T.	300,0	cbm

Side Thruster		
Bow Thruster	1.800	kw
Stern Thruster	not fitted	kw

Car Handling Equipments		
Stern Quarter Ramp		
Position	Starboard Quarter	
Size	31,5 x 7.5m driveway width	
Opening Size	12 m (B) x 5.4m/3.34/2.80 (H)	
Load Base	150	tons
Side Ramp		
Position	Starboard	
Size	21.5 x 4.5 driveway width	
Opening Size	5,4 (B) x 5.88/2.8/3.34	
Load Base	22	tons

Cargo Capacity					
Deck	Clear height (mm)	Type of deck	SQM	Axle load (t)	Uniform load (tons/m²)
12	2000	Fixed	5572	1,6/2	0,25
11	2000	Fixed	5716	1,6/2	0,3
10	2000	Fixed	5716	1,6/2	0,25
9	2200	Fixed	5716	1,6/2	0,3
8	1700/2100	Liftable	5716	1,6/2	0,3
7	2200/2600/4300	Fixed	4998	15/2	0,75
6	1900/2400	Liftable	5294	1,6/2	0,3
5	2800/3340/5200	Fixed	5133	25/2 & 55/4	2,5
4	2400	Liftable	3645	16,2	0,3
3	2200/4600	Fixed	3551	15/2 & 25/4	2
2	1700	Liftable	3046	1,6/2	0,3
1	2000/3700	Fixed	2691	15/2	1
Total m²			56.794		